

**Cost of testing of oil and cellulose insulation at the Materials testing laboratory of SEC
"ZTZ-SERVICE"**

2026-01-05

Parameter	Price for 1 test, UAH, VAT exc.
1 Colour	
2 Acidity	
3 Content of water-soluble acids	
4 Interfacial tension	
5 Saponification value	
6 Inhibitor content	
7 Aromatic hydrocarbon content	
8 The content of aging products in the IR spectrum	
9 Removing the IR spectrum with calculations	
10 Sediment and soluble sludge	
11 Light absorption coefficient (turbidity)	
12 Refractive index	
13 Density	
14 Viscosity	
15 Viscosity at subzero temperatures	
16 Flash point	
17 Corrosive sulfur (100 °C, 3 h.)	
18 Corrosive sulfur (150 °C, 48 h.)	
19 Water content	
20 Oil moisture content	
21 Particles content	
22 Appearance	
23 Particles content under a microscope	
24 Dielectric dissipation factor	
25 Resistivity	
26 Factor of Polarity	
27 Breakdown voltage	
28 Dissolved gas analysis	
29 Content of furan compounds	
30 Oxidation stability of GOST	
31 Residual oil life	
32 Water content of cellulose insulation	
33 Degree of polymerization	
34 Moisture content of sorbents	

Prices are in UAH including 20% VAT.

When ordering work, ask for confirmation of current prices.

**Head of Materials Testing Laboratory LLC "Research
Center "ZTZ-SERVICE"**

Yu.V.Vinogradova